

<b>BONAPLAST PACKAGING INDUSTRY</b>	<b>SAFETY AND QUALITY FORM</b>	Code: E.01.29 Publication No: 03 P.: 1 To:1
	<b>PRODUCT DISCRIPTION</b>	

**BUCKET FA 1.2 (X2) – LID FA 1.2 (X2)**

<b>TECHNICAL SPECIFICATION BUCKET</b>		<b>TECHNICAL SPECIFICATION LID</b>	
UPPER EXTERNAL DIAMETER (mm)	131	DIAMETER (mm)	128
UPPER INTERNAL DIAMETER (mm)	123	HEIGHT (mm)	9.6
BOTTOM'S DIAMETER (mm)	105	THICKNESS (mm)	0.6
HEIGHT (mm)	131.5	WEIGHT / VARIATION (+/- 2.5%)	11 gr
WALL THICKNESS (mm)	0.6	LID PACKAGING	1500 pcs / carton 30000 pcs / pallet 13500 pcs / europallet
BOTTOM'S THICKNESS (mm)	0.65	<b>CAPACITY (LT)*</b>	
BUCKET WEIGHT/VARIATION (+/- 2.5%)	36 gr (plastic handle included)	VOLUME TO RIM 1.000	BRIMFULL VOLUME 1.200
PRINTING DIAMENSIONS (OFFSET) (HEIGHT * WIDTH)	-	STACKING	5 per Height
PRINTING DIAMENSIONS (IML) (HEIGHT * WIDTH)	126,53 mm * 374,63 mm	<b>CERTIFICATIONS</b>	
BUCKET PACKAGING	375 pcs/carton 3750 pcs/pallet, 3375 pcs/europallet	ISO 9001:2015 / ISO 22000:2018/FSSC 22000	
<b>OVERALL MIGRATION TESTS LIMITS EU REGULATION 10/2011 / DIRECTIVE 94/62 / EC (Article 11)</b>		<b><u>USEFUL STORAGE INFORMATION</u></b>	
<ul style="list-style-type: none"> <li>• Overall Migration (Simulant A: ethanol 10%)</li> <li>• Overall Migration (Simulant B: acetic acid 3% w/v)</li> <li>• Overall Migration (Simulant D2: Vegetable Oil)</li> <li>• Sum of Heavy Metals</li> </ul>		To maintain the quality of this product, it is recommended to store it in its original packaging, away from any source of local heat and humidity, away from direct sunlight (below 30 ° C) and dry conditions. It is recommended to allow the product to reach operating temperature 24 hours before use.	

**Microbiological Hazards:** None **Natural Hazards:** None

**RAW MATERIALS:** PP, Color for PP, Plastic Bags, IML Labels Compliant with European Food Regulations EU No 10/2011 (14.01.2011), EC No 2023/2006.

**SML:** EU / EFTA regulatory framework No 10/2011

**\*Capacity assessment was made with water**